

ACCTUAL TORQUE CONTROL

▸ Features

- Visual position indicator
- Quick-Set cam
- 8 points terminal strip
- Two cable entries
- Captive cover bolts
- ISO5211 bracket



▸ Specification

Model	BMLS
Enclosure	Weatherproof, IP67
Temperature Range	-20 ~ 85
Cable Entry	2 x 1/2" PF (PT) (NPT)
Terminal Strip	8 Points
Position Indicator	0° ~ 90° : Yellow for Open, Red for Closed
Switch Type	2SPDT Mechanical switches (Proximity sensors *Option)
Painting	Polyester powder coating
Bracket	Plastic, steel

▸ Mounting Bracket

- * BMLS provided with bolts, nuts and can choose one of PB1 or SB1
- * BMLS-EX provided with bolts, nuts and AB1
- * Other brackets are option

	Model	Material	Size				
	PB1 (BMLS, BMLS-EX)	Plastic (ABS)	30 x 80 H:20		SB3 (BMLS-EX)	Steel	30 x 130 H:30
	SB1 (BMLS)	Steel	30 x 80 H:20~30		SB4 (BMLS-EX)	Steel	30 x 80 H:30
	SB2 (BMLS-EX)	Steel	30 x 80 H:20				